



EP
Let's grow together

Tractor de Arrastre QDD10

Tractor Eléctrico Capacidad 1Ton.

- Ideal para tareas en el Retail y Plataformas de Entrega.
- Aplicable para las Industrias de Retail, Aeropuertos y Logística.

Tractor de Arrastre QDD 1.0Ton.

| Distinguishing mark | | | | |
|---------------------|--|---------------------------------|--------|----------------|
| 1.1 | Manufacturer | | | EP |
| 1.2 | Model designation | | | QDD10 |
| 1.3 | Drive unit | | | Electrics |
| 1.4 | Operator type | | | pedestrian |
| 1.5 | rated capacity | Q | t | 1 |
| 1.7 | Rated drawbar pull | F | N | 200 |
| 1.9 | Wheelbase | y (mm) | mm | 315 |
| Weight | | | | |
| 2.1 | Service weight ¹ include battery ² | | kg | 98 |
| 2.2 | Axle loading, laden driving side/loading side | | | 98/0 |
| 2.3 | Axle loading, unladen driving side/loading side | | kg | 78/20 |
| Types,Chassis | | | | |
| 3.1 | Tyre type driving wheels/loading wheels | | | rubber |
| 3.2 | Tyre size, driving wheels ¹ diameter×width ¹ | | mm | 2x Φ250x85 |
| 3.3 | Tyre size, loading wheels ¹ diameter×width ¹ | | mm | 2x Φ75x32 |
| 3.5 | Wheels, number drivingr/loading (x=drive wheels) | | mm | 2x /2 |
| 3.6 | Track width, front,driving side | b ₁₀ (mm) | mm | 428 |
| 3.7 | Track width,rear,loading side | b ₁₁ (mm) | mm | 217 |
| Dimensions | | | | |
| 4.8 | standing height | h ₇ (mm) | mm | — |
| 4.9 | Height drawbar in driving position min./max. | h ₁₄ (mm) | mm | 835□ 930□ 1010 |
| 4.12 | Tow coupling height scope | h ₁₀ (mm) | mm | |
| 4.19 | Overall length | l ₁ (mm) | mm | 1255~1315~1345 |
| 4.21 | Overall width | b ₁ / b ₂ | mm | 520 |
| 4.32 | Ground clearance, center of wheelbase | m ₂ (mm) | mm | — |
| Performance data | | | | |
| 5.1 | Travelspeed, laden/ unladen | | km/ h | 4.5/5 |
| 5.5 | Drawbar pull, laden/unladen | | N | 200 |
| 5.6 | Max. drawbar pull, laden/unladen | | N | 650 |
| 5.7 | Gradeability, laden/unladen | | % | 3/16 |
| 5.10 | Service brake type | | | Mechanical |
| Electric-engine | | | | |
| 6.1 | Drive motor rating S2 60 min | | kW | 0.4 |
| 6.3 | The maximum allowed size battery | | mm | 196/165/175 |
| 6.4 | Battery voltage/nominal capacity K20 | | V/ Ah | 2x12/50 |
| 6.5 | Battery weight | | kg | 2x19 |
| Addition data | | | | |
| 8.1 | Type of drive unit | | | DC |
| 10.5 | Steering type | | | Mechanical |
| 10.7 | Sound pressure level at the driver's ear | | dB (A) | 74 |
| 10.8 | Towing coupling, type DIN 15170 | | | — |

1.The parameters in the table are of the standard model. For more information, please contact us.

2.The parameters are subject to change without notice.

Soluciones de Paquetería



- Gran flexibilidad con mínimo volumen para arrastrar carros de alambres.
- Fuerte tracción
- Operación estable
- Fácil de Cargar
- Manubrio ajustable

